

















ESD Control & Monitoring

Impedance Meter • TwinGuard Wrist Strap Continuous Monitor • ESD Turnstile Entry System • Megalin ESD Tester • Megalin Data Logging Tester • Integrated Management Software with Megalin Tester (GZ350 & GZ600) • Electrostatic Image System • E-ReticleTM • Dickson Temperature & Humidity Data Logger

Impedance Meter

This instrument is designed to measure generic AC impedance per ANSI/ESD S20-2007 and IEC-61340-2007 standards.

- Portable and light weight
- Built in memories for data storage / recording
- Built in SD card slot for measurement data transfer
- AC impedance range: $0\Omega 20m\Omega$




TwinGuard Wrist Strap Continuous Monitor

TwinGuard is a dual channel continuous wrist strap monitor and provide constant monitoring on operator's grounding through wrist strap or ankle strap.







ESD Turnstile Gate System



Turnstile Models


Mini Tripod ZT-TP-MS









Standard Tripod ZT-TP-MD-01









Retracting Arm Gate ZT-ADA-DA-2000








Retracting Flap Gate ZT-AFB-AR-S01







Megalin ESD Tester

- ESD Testing Made EASY
- Digital Measurement & Calibration
- Digital Readout LCD Model
- Flexible Limit Configurable





- LCD Test results Display Models
- Data logging version available
- Relay out available for immediate entry system integration
- Support Common Card Systems for Data logging





Megalin Data Logging Tester

- Huge Buffer Memory Storage Up to 5000 Test records
- Records Test Data, employee records and Time stamp
- Auto Time Synchronization
- Testing and Data logging continues even when Server or LAN down.
- Data transfer resumes when LAN or Server is back to operation
- Card system support Majority of Common Card System (HID, Mifare, Temic, EM)




Integrated Management Software with Megalin Tester (GZ350 & GZ600)

- Auto Manage all employee data
- Auto importing the latest information on a location
- Auto Report emailing after subscription to the report
- Multi-client installation allow all to access the information
- Real MS SQL Data base System, where there is no data limit
- Real LAN interface Low LAN Traffic Resource
- Email Alert on failures








Electrostatic Image System



Linear Type with LED Display (DYEQ01-HW-HSK5008DL)


This instrument is designed to measure and monitor electrostatic charge distribution on material/surface.

- Portable and non-contact monitor
- Software capable to capture real time imaging system and data logging.
- Portable Linear type and Area type with LED display.
- Validate changes over surface charge instantly.



Area Type with LED Display (DYEQ01-HW-HSK5064DA)







E-Reticle™

- In-Situ measurement of electric fields in production reticle environment.
- Ideal for mask fab or wafer fab ESD and EFM risk assessment.
- Data Analysis software allow user to quickly assess ESD risks.

E-Reticle™ on 8 inch SMIF Docking station without pod



E-Reticle™ Backside view



E-Reticle™ 8 inch SMIF Docking Station



Dickson Temperature & Humidity Data Logger

Ethernet/Wireless 2.4 GHz version (Wizard 2 series)

- Uses Wizard2 Data logging Software
- Email Alarm Alert
- Comes in 2.4 Ghz Wireless or Ethernet Version









Ethernet / WIFI Cloud Version (DicksonOne series)

- Uses DicksonOne Cloud base Data logging
- Email Alarm Alert
- Comes in Wifi or Ethernet version









Standard USB / SD card Interface (Dicksonware Software)

- Simple SD Card Data Transfer or USB Data
- Simple Data logging Operating Software (Dicksonware)










Touch Screen / USB / SD Card Interface (Dicksonware)

- Simple SD Card Data Transfer or USB Data
- Simple Data logging Operating Software (Dicksonware)







ESDeqpmt201402EN_S2BENSON



2304 Bedok Reservoir Road, Bedok Industrial Park C, Singapore 479223 Tel: +65 6444 2678 | Fax: +65 6743 7172 | Web: www.douyee.com Email: s2_marketing@douyee.com.sg