



Ceiling Emitter

MODEL 5509E

In a matter of seconds, the Model 5509e ceiling ionization system eliminates electrostatic discharge and particle contamination caused by electrostatic attraction. The 5509e ceiling emitters are designed to provide uniform ionization throughout the open areas of a cleanroom. Mounted onto the ceiling surface or inside a flush mount channel, Model 5509e ceiling emitters maintain aesthetics without disrupting cleanroom laminar airflow or compromising the integrity of operating class 1 cleanrooms.

Model 5509e ceiling emitters use pulsed DC ion emission with ion regulation, making output and balance adjustments possible at each emitter. Depending on the amount of ionizers per room, the Model 5509e works with either the Model 5024(e) or 5084(e) controller. Timing and output can be controlled through the hand-held Model 5080 Input Module.

Features


- Low voltage operation (24 VAC)
- Individually adjustable ion emission output
- Feedback with alarms available at each emitter
- Pulsed DC technologies with local and system-wide adjustment controls
- Available with single crystal silicon emitter points

Benefits

- Safe, reliable operation
- Balance can be fine-tuned beneath each emitter
- Enhanced performance and stability
- Optimizes ionization efficiency in varying airflows
- Industry standard, cleanest available emitter point material



Specifications

Input Voltage	24 VAC, 50/60 Hz, 1.25W
Control Signal	±10 VDC control signal from a 5024(e) or 5084e controller
Output Voltage	0-18 kVDC, ±10% for each polarity; positive and negative output levels adjusted centrally at controller and locally at each emitter
Output Current	<15 mA; current and voltage limited to eliminate shock hazard
Connectors	Telephone type RJ-11 modular jack receptacle on each end of emitter
Output Control	Each emitter has controls that independently adjust both positive and negative output
Regulation	Output and balance stability is achieved by independently regulating the ion emission voltage of each polarity at each emitter
Timing	Precise timing (0-10 sec) is supplied by the controller. LEDs on each emitter indicate the polarity of the ion emission
Ion Emission	Pulsed DC
Emitter Points	Single crystal silicon, machined titanium, or tungsten alloy; all emitter points are replaceable; estimated emitter point life varies from 2-3 years depending on material used
Calibration	Annually, semi-annually, or quarterly depending on manufacturing sensitivity
Ozone	<0.005 ppm
EMI	Below background level
Alarm	Visual alarm, red LED located in the middle of the emitter chassis indicates an alarm condition; audible alarm, sounds at the 5024e/5084e controller when an alarm event occurs at any emitter
Mounting	A variety of surface and flush mounting methods and brackets is available, including cleanroom-compatible interlocking self-adhesive mounts (3M TYPE SJ 3551)
Emitter Rods	Available in 2.5, 5, 10, 15, 24, 36, or 60 in. lengths (63.5, 127, 254, 381, 609, 914, 1524 mm)
Dimensions	1.25H x 1.5D x 17.5L in. (3.2 x 3.8 x 44.5 cm)
Weight	1.4 lb (0.5 kg)
Components Required	Model 5024(e) or 5084(e) Controller
Warranty	2 year limited warranty
Certifications	

Ordering Information

91-5509EC-XX-SDL	Emitter with titanium emitter points in 2.5, 5, 10, 15, 24, 36, or 60 inch rod lengths
91-5509EU-XX-SDL	Emitter with silicon emitter points in 2.5, 5, 10, 15, 24, 36, or 60 inch rod lengths
91-5024-CER	Model 5024 Controller, supports up to 4 emitters
91-5024E-CER	Controller with alarm, supports up to 20 emitters
91-5024E-CE-ALMR	Controller with audible alarm, supports up to 20 emitters
91-5084E-CE	Controller with alarm, supports up to 80 emitters
91-5080	Model 5080 Handheld Terminal for Model 5084 Controller

Designed for Flexibility

The Model 5509e Ceiling Emitter's compact design is compatible with any cleanroom ceiling system, whether surface mounted or recessed. The ionizer's modularity, with removable emitter rods, makes it practical in today's cleanrooms, where equipment is periodically moved.

Quality to Depend On

In addition to the advanced features mentioned above, the 5509e ceiling emitter represents the same quality and reliability people expect from Simco-Ion. Simco-Ion has set the standard for over 15 years with leading-edge room ionization systems, and industry-best reliability.



The Model 5509e has several options for emitter rod size. Its modular design makes it easy to exchange one size for another to accommodate a variety of cleanroom conditions.

SIMCO ION™
An ITW Company

DS-5509_V5 - 08/11
© 2011 Simco-Ion
All rights reserved.

Simco-Ion

Technology Group
1750 North Loop Rd., Ste 100
Alameda, CA 94502

Tel: 800.367.2452 (in USA)
Tel: 510.217.0600

ioninfo@simco-ion.com
www.simco-ion.com