



# Point of Use Ionizing Blower

## MODEL 6432e

The Point of Use Ionizing Blower Model 6432e control static discharge in assembly, inspection, packaging areas, and in-tool wherever static build-up can cause contamination, ESD, material-handling problems or microprocessor lock-up.

IsoStat technology provides several useful benefits for the 6432e blower. It's small size and ability to operate in balance without grounding wires or cables allows easy and quick installation and setup. The blower's internal emitter points are electrostatically shielded to eliminate field-induced charging. Steady-state DC operation provides fast discharge with low airflow for greater operator comfort.

### Features






- IsoStat® technology
- Steady-state DC ion emission
- 24 VDC or 24 VAC input power
- Facility Monitoring System (FMS) interface
- Operational failure alarm
- Small footprint design with in-tool stand or benchtop stand

### Benefits

- Intrinsically balanced; no calibration needed
- Minimum ion recombination provides maximum static control
- Convenient power options, wall-provided AC or tool-provided DC
- Faster response to ionization failure with notification through tool or facility monitoring system
- Provides visual notification of any operational failures
- Occupies little work or tool space; cleanroom-compatible (minimizes disruption of laminar flow)



## Specifications

<b>Input Voltage</b>	24 VDC (±10%), 6W max or 24 VAC (±10%), 50-60 Hz, 6W max
<b>Indicators</b>	Green power LED; red alarm LED
<b>Ion Emission</b>	Steady-state DC
<b>Emitter Points</b>	Tungsten wire; internally shielded
<b>Airflow</b>	49 CFM (typ)
<b>Discharge</b>	±1000-100V <4 sec @ 1 ft <sup>1</sup> (using 24 VAC)
<b>Balance</b>	±20V @ 1 ft away
<b>Cleanroom Class</b>	Meets ISO 14644-1 Class 5 (Fed Std. 209E Class 100)
<b>Ozone</b>	<0.005 ppm, typical (24-hour accumulation)
<b>Mounting</b>	Small in-tool bracket/stand (1.8 x 5.1 in./45 x 129 mm); large benchtop stand (4.1 x 5.1 in./108 x 129 mm); both with 1/4" mounting hole and 10-32 truss head screws
<b>Dimensions</b>	5.3H x 5.0W x 2.5D (133 x 127 x 63 mm); small bracket base is 1.8 in. (45 mm); large stand base is 4.1 in. (108 mm)
<b>Weight</b>	21 oz (595g) with large stand
<b>Warranty</b>	2-year warranty
<b>Certifications</b>	
<b>Transformer 14-1320</b>	
<b>Input Voltage</b>	120 VAC ±10%, 50-60 Hz
<b>Output</b>	24 VAC, 60 Hz @ 450 mA, ±5%
<b>Dimensions</b>	2.4H x 2.2W x 1.6D in. (61 x 56 x 41 mm)
<b>Certifications</b>	
<b>Transformer 14-1330</b>	
<b>Input Voltage</b>	230 VAC ±10%, 50 Hz
<b>Output</b>	24 VAC @ 750 mA, ±5%
<b>Dimensions</b>	2.8H x 2.5W x 1.9D in. (71H x 64W x 48D mm)
<b>Certifications</b>	
<b>AC Adapter 14-1322</b>	
<b>Input Voltage</b>	120-240 VAC ±10%, 50/60 Hz
<b>Output</b>	24 VDC @ 400 mA
<b>Dimensions</b>	1.4H x 2.1W x 3.4L in. (36H x 53W x 86L mm)
<b>Certifications</b>	 

1. Tested in accordance with ANSI/ESD STM3.1-2006.

## Enhanced Features

The Model 6432e offers both an alarm LED on the front of the blower that indicates a high voltage circuitry failure, and a five-pin facility monitoring system (FMS) interface. The FMS interface provides a 4-20 mA current loop and relay output connection. Together with the 24 VDC input connection, the FMS output is situated on a convenient terminal block, designed for easy integration with your process equipment.



## Power Options

For increased flexibility, the Model 6432e Blower can be directly powered by process equipment or 24 VDC/VAC power to fit the needs of your environment. For 100-120 VAC input power, use transformer #14-1320; for 240-260 VAC, use #14-1330; for applications where DC input power is preferable, use AC/DC adapter #14-1322.



The Model 6432e is offered with a smaller in-tool stand (shown here) or a larger benchtop stand, shown in the photo on the front of the datasheet.

## Ordering Information

92-6432e-US	6432e Ionizing Blower; benchtop stand; 120 VAC to 24 VAC transformer
91-6432e	Blower with alarm indicator light and FMS
32-6433	Benchtop stand
32-6434	In-tool stand
14-1320	24 VAC 120V 60 Hz transformer
14-1330	24 VAC 230V 50 Hz transformer
14-1322	24 VDC 120/230V 50/60 Hz AC-DC adapter

**SIMCO ION**<sup>TM</sup>  
An ITW Company

DS-6432\_V9 - 08/11  
© 2011 Simco-Ion  
All rights reserved.

**Simco-Ion**  
Technology Group  
1750 North Loop Rd., Ste 100  
Alameda, CA 94502  
Tel: 800.367.2452 (in USA)  
Tel: 510.217.0600  
ioninfo@simco-ion.com  
www.simco-ion.com