GZ-3000 Ground Ranger Impedance Meter

Features:

- Patented design Measurement Technology
- High/ Low and Near Fail limit setting
- LCD back-lighted display with 0.01Ω resolution.
- Light weight and Easy to operate with Data Recording
- Data logging with addition Data fields for
 - >> Operators
 - >> Locations
 - >> Test results.
- Built-in Memories for Data Storage/Recording
- Built-in SD Card Slot for Measurement Data Transfer
- Long-life rechargeable battery provide convenient and cost savings
- AC impedance measurement range: $0\Omega \sim 20M\Omega$.
- Auto Power Saving Setting at 5 min idle time for more power saving
- Digital Calibration High accuracies and repeatability
- Free Utility program for Paperless Report generation

Product Specifications

Dimension : 18 x 12 x 3 cm

Weight : 150g

Power Source : 100-240VAC/ 50-60Hz/ 500mA

Power Status Indicator : Battery Low LED Indicator

: $0\Omega \sim 20M\Omega$. Impedance Range

Hardware interface : RS232 & Built in SD Slot Download type : SD Card Data transfer

Battery Type : Rechargeable Lithium Ion Battery

: Back Light LCD Display 4 Lines x 20 Char Display

> **OK LED indicator** NG LED indicator

Low Batt LED indicator

Optional Accessories

Calibration Software RS232 interface cable

Decade Resistance Box Calibrator



DOU YEE ENTERPRISES (S) PTE. LTD

2304 Bedok Reservoir Road, Bedok Industrial Park C, Sinagpore 479223

Tel: (+65) 64444 2678 Email: marketing@douyee.com.sg Fax: (+65) 6743 7172 Website: www.douyee.com





